

## Self-Closing Sliding Door

# HD



# Comfortable, noiseless and secured operation

## ■ A fully opened stopper comes as a standard equipment

This is convenient when carrying out huge luggage through the doorway.



## ■ Easy inspection, maintenance and repair



Adjustment and inspection of hanger part and self-closing device can be conducted quickly and easily.

※Please always consult with us when adjustment, inspection and repair is needed.



## ■ Door handle is positioned to be used easily by everyone

With a Universal Design perspective, the position of the handle is set at a height of 700~1100mm, which can be easily operated by anyone.

## ■ Safety considered foot step



There is no floor railing required for this sliding door, and the opening width of a single sliding door can be up to 1300mm: therefore, wheelchair, bed, and large luggage can easily go through the doorway.

## ■ Endurance test

Endurance tests of door opening/closing are conducted for 5 hundred thousands time to confirm reliability and durability of HD series. (House test)

## ■ Initial opening force<sup>※</sup> 8.6N (0.88kg·f)

### Data of test body

Initial opening force	8.6N(0.88kg·f)
Effective aperture width	1200mm
height	2100mm
Door gravity	47kg

※Force that occurred when the sealed door is moving.

Note) Above data is an actual value at the test site, please note that this is not a guaranteed value.

Reference : The required force to open a car door is 14.7N (1.5kg·f)





Showroom  
Jl. Tomang Raya No. 15, Jakarta 11440, Indonesia  
p. (+62-21) 5601078/9

Branch:  
Jl. Ngemplak 30, Komp. Ambengan Plaza Blok B No. 21  
Surabaya, Indonesia  
p. (+62-31) 5451133 (Hunting), (+62-31) 5459331