

# Data Sheet

## WÖHR COMBILIFT 542



### Platform load options:


- max. 2000 kg, load per wheel 500 kg
- max. 2600 kg, load per wheel 650 kg **1**
- max. 3000 kg, load per wheel 750 kg **1**

### Platform load can be increased later (also individual parking places)


### Platforms are in horizontal position to drive on

### Grid arrangement:

- minimum 2 grids for 3 vehicles
- maximum 10 grids




The vehicle on parking place 7 is requested. The parking places 2, 4 and 6 are shifted to the left.



Parking place 7 is lifted up to the entrance level (EL), the vehicle is now ready for exit.

### Length dimensions underground car park (height dimensions see page 2)



**1** Increasing of platform load at extra cost

**2** Drainage channels (performed by the customer):  
 - 10 x 2 cm, with a 50 x 50 x 20 cm drainage pit  
 - in case of installation of a sump pump, it is necessary to comply with the drainage pit dimensions specified by the pump manufacturer

**3** Channels or undercuts/concrete haunches (performed by the customer):  
 - not allowed along the pit floor-to-wall joints  
 - should channels or undercuts be necessary, the system width needs to be reduced or the pit needs to be wider

**4** 500 cm vehicle length = 550 cm pit length (including doors)  
 520 cm vehicle length = 570 cm pit length (including doors)

**5** Free spaces:  
 - please ask WÖHR for the dimension sheets

**6** Doors (see page 5/6)


**7** In this area, 0% of downward/upward slope in longitudinal and cross direction

**8** For above ground garages with a slope, a drainage channel in the driveway is recommended

### Dimensions

- all dimensions specified are the minimum, finished dimensions
- tolerances must be taken into consideration
- all dimensions are given in cm

**Height dimensions**



Type	Pit depth A	Vehicle height LL (lower level)	Vehicle height EL (entrance level)				
			200	205	210	215	220
			Height H				
542-175	175	150	220	225	230	235	240
542-180	180	155	220	225	230	235	240
542-185	185	160	220	225	230	235	240
542-190	190	165	220	225	230	235	240
542-195	195	170	220	225	230	235	240
542-200	200	175	220	225	230	235	240
542-205	205	180	220	225	230	235	240
542-210	210	185	220	225	230	235	240
542-215	215	190	220	225	230	235	240
542-220	220	195	220	225	230	235	240
542-225	225	200	220	225	230	235	240
542-230	230	205	-	225	230	235	240
542-235	235	210	-	-	230	235	240
542-240	240	215	-	-	-	235	240
542-245	245	220	-	-	-	-	240

### Decision support for the vehicle height

Choosing the right vehicle height for your project is essentially based on any building regulations, user expectations and building specifications. Criteria can include:

**Residential buildings:**

Different parking space heights are conceivable and can affect the sales price. For example, lower parking spaces could be provided for higher vehicles. This results in more convenient access to the vehicle. Less high vehicles in the upper parking spaces and thus reduced building height and less enclosed space. The ramp to the underground car park will be less steep or less long. To make it easier to sell parking spaces, we recommend that the vehicle heights be the same.

**Office buildings:**

For this parking concept, we recommend the same vehicle height for all parking spaces. If permanently assigned parking spaces are preferred for parking permittees, different parking space heights could be provided.

**Hotels:**

Whether city hotel, vacation hotel or vacation apartments: With changing occupancy, all parking spaces should have the same vehicle height. Maximum parking space heights should be selected to allow parking for vehicles with roof-mounted structures, if necessary.

### Configuration example residential buildings

1	Vehicle height EL	205 cm	3	Type	542-190
2	Vehicle height LL	165 cm	4	Pit depth A	190 cm
			5	Height H	225 cm

Type	Pit depth A	Vehicle height LL (lower level)	1 Vehicle height EL (entrance level)				
			200	205	210	215	220
			Height H				
3 542-185	4 185	2 160	220	5 225	230	235	240
542-190	190	165	220	225	230	235	240
542-195	195	170	220	225	230	235	240

### Configuration example office building and hotels

1	Vehicle height EL	205 cm	3	Type	542-230
2	Vehicle height LL	205 cm	4	Pit depth A	230 cm
			5	Height H	225 cm

Type	Pit depth A	Vehicle height LL (lower level)	1 Vehicle height EL (entrance level)				
			200	205	210	215	220
			Height H				
3 542-225	4 225	2 200	220	5 225	230	235	240
542-230	230	205	-	225	230	235	240
542-235	235	210	-	-	230	235	240


### Vehicle heights

The following table is intended as a guide to help you select the platform distance and construction dimensions:

Aston-Martin DBX	168 cm	Dacia Duster	170 cm	Porsche Cayenne Coupé	168 cm
AUDI A6	151 cm	Ford Galaxy	175 cm	Porsche Macan	162 cm
AUDI Q4	163 cm	Ford Kuga	167 cm	Skoda Kodiak	168 cm
AUDI Q7	174 cm	Jaguar F-Pace	166 cm	Tesla Model X	168 cm
Bentley Bentayga	173 cm	Landrover Defender	198 cm	Toyota Highlander	173 cm
BMW iX	170 cm	Maserati Levante	169 cm	VW Sharan	174 cm
BMW X3	166 cm	Mercedes G-Class	195 cm	VWT 3	196 cm
BMW X5	176 cm	Mercedes GLE Coupé	173 cm	VW Tiguan	167 cm
BMW X6	176 cm	Mercedes V-Class	191 cm	VW Touareg	170 cm

All vehicle heights are non-binding, due to the wide range of model variants and the year of construction.

**Clearance profile (for standard vehicles)**



\* for a 250 cm platform width  
 \*\* The overall vehicle height including roof luggage rails and antenna mounts must not exceed the max. vehicle height dimensions specified  
 \*\*\* see page 1


**Width dimensions**

Platform widths:

- 250 cm:
  - for 190 cm vehicle width (without outside mirror)
- 260-300 cm:
  - for vehicles wider than 190 cm (without outside mirror)
- 270-300 cm:
  - for units at the end of the driving aisle


For comfortable parking, entry and exit conditions platform widths of 250 cm are recommended. Reduced platform width means reduced parking comfort depending on the vehicle width, vehicle type, individual driving style, access situation of the garage.  
 With a 90° arrangement of the parking places, we recommend widening the driving aisle or a wall recess (see below).

**Width dimensions (underground car park)**



↔ EL (entrance level) 1 2


↕ LL (lower level) 2



Space requirements		clear platform width
B	B1	
280	270	250
290	280	260
300	290	270
310	300	280 ③
320	310	290 ③
330	320	300 ③

- 1 One entry/exit is required on entrance level (EL) for each grid
- 2 For a comfortable parking process and comfortable conditions for getting in and out of the car, we recommend platform widths of at least 250 cm. Smaller platform widths are possible but not recommended (please contact WÖHR).
- 3 Platform load max. 2600 kg
- 4 It is not possible to combine different platform widths

**Wall recess**



According to GaVo for Baden-Württemberg (07.07.1997/26.01.2011):  
 For parking places with a 90° arrangement at the end of the driving aisle, the entrance width must be min. 275 cm.  
 At the end of the driving aisle, we recommend to provide a wall recess, if technically possible.

**Doors**


According to DIN EN 14010 doors are required.

Automatic sliding doors:

- electrical drive
- controls are integrated in the overall system
- electro-mechanically interlocked
- can only be opened when the selected parking place has reached the entry/exit position
- any crash openings are closed in the entrance area


Local requirements for electrical doors regarding the technology, maintenance and revision are not subject of our delivery. These matters have to be observed and carried out by the customer, according to the local regulations.

**Sliding doors behind the building pillars with door offset**




Space requirements B4	clear platform width
520	250
540	260
560	270
<b>580</b>	<b>280</b> ②
<b>600</b>	<b>290</b> ②
<b>620</b>	<b>300</b> ②

- ① The driving aisle width must comply with local regulations
- ② Platform load max. 2600 kg




H1	Vehicle height EL (entrance level)				
	200	205	210	215	220
H1	220	225	230	235	240

**Sliding doors below the lintel between the building pillars**




Space requirements B4	clear platform width
520	250
540	260
560	270
<b>580</b>	<b>280</b> ②
<b>600</b>	<b>290</b> ②
<b>620</b>	<b>300</b> ②

- ① The driving aisle width must comply with local regulations
- ② Platform load max. 2600 kg




H2	Vehicle height EL (entrance level)				
	200	205	210	215	220
H2	220	225	230	235	240

## ■ Sliding door floor guides




- ① Finished floor:
  - compliant to DIN 18353,
  - floor evenness compliant to DIN 18202, table 3, line 3
- ② Floor guide section:
  - base plate with plastic rollers
  - fixed on the floor with adhesive anchor (M8 internal screw thread)
  - borehole depth approx. 9 cm
  - in the event that floor filling needs to be laid into the door section to the purpose of reaching the required floor evenness, the borehole depth needs to be increased by the thickness of the floor fill (max. 4 cm)
- ③ If the driving aisle is made of concrete blocks, asphalt etc., the concrete slab of the pit edge in the door area must be min. 27,5 cm wide



**Static calculations and construction works requirement**

Section



542 (2000 kg)	
P1	+ 38,0 kN*
P2	+ 19,0 kN
P3	± 2,5 kN
P4	± 20,0 kN
P5	± 10,0 kN

542 (2600 kg)	
P1	+ 46,0 kN*
P2	+ 23,0 kN
P3	± 2,5 kN
P4	± 24,0 kN
P5	± 12,0 kN

542 (3000 kg)	
P1	+ 52,0 kN*
P2	+ 26,0 kN
P3	± 2,5 kN
P4	± 26,0 kN
P5	± 13,0 kN

\*specified load bearing data includes the vehicle weight

Type	A	B
542-175	145	158
542-180	150	163
542-185	155	168
542-190	160	173
542-195	165	178
542-200	170	183
542-205	175	188
542-210	180	193
542-215	185	198
542-220	190	203
542-225	195	208
542-230	200	213
542-235	205	218
542-240	210	223
542-245	215	228

Fixing of the system frames to the floor slab:

- using base plates (approx. 350 cm<sup>2</sup>)
- using adhesive anchor bolts
- hole depth to 12- 14 cm
- bottom plate in concrete
- thickness of bottom plate min. 18 cm

Fixing of the system frames to the walls:

- with walls plates (approx. 30 cm<sup>2</sup>)
- using adhesive anchor bolts
- hole depth to 12- 14 cm
- front drive-in wall and rear wall in concrete
- perfectly flat wall surfaces
- without protruding sections such as border edgings, pipes and tubes, etc.
- thickness of walls min. 18 cm

Concrete quality grade:

- compliant to the static requirements of the construction
- min. C20/25 grade (for dowel fastening)


Frame bearing points:

- the specified lengths are expressed as mean value
- for the exact data, specific TÜV-tested data sheets are available

Door widths/widths of columns:

- please contact WÖHR
- grid width (270/280/290/300/310/320) must be observed

Ground plan




Space requirements				clear platform width
B	B1	B2	B3	
280	270	250	520	250
290	280	260	540	260
300	290	270	560	270
310	300	280	580	280 ②
320	310	290	600	290 ②
330	320	300	620	300 ②

- 1 If the width of the pillars is more than 20 cm, than the width of the drive through will be reduced accordingly to the above mentioned width dimensions (B and B1). In order to avoid this, we recommend to extend the measures between the pillars (B2 and B3) accordingly. Please contact WÖHR.
- 2 Platform load max. 2600 kg

**Electrical specifications**

**Installation diagram**



Cabling preparation to be performed by the customer:

- up to the main switch to be in place prior to starting the installation operations
- connection to the main switch during installation
- system functional check testing can be performed by WÖHR together with the electrician provided by the customer
- if requested at a later date, functional check testing can be performed by WÖHR at extra-cost

Grounding and potential equalisation:

- to be performed by the customer compliant to DIN EN 60204
- connections required every 10 metres

**To be performed by the customer**

Item	Quantity	Description	Position	Recurrence
1	1 piece	power meter	in the feed cable	
2	1 piece	fuse protection or automatic circuit breaker compliant to DIN VDE 0100 part 430: - 3 x 16 A (11 KW) slow blow (starting current 24 A) with only one power pack per system	in the feed cable	1 x per power pack
3	based on site conditions	compliant to local power supply regulations 3 phases + N + PE* 230/400 V, 50 Hz	feed cables to main switch including connection	1 x per power pack
4	every 10 m	grounding and potential equalisation lead-out connection	along pit floor edges/rear wall	
5	1 piece	grounding and potential equalisation compliant to DIN EN 60204	from lead-out connection to system	1 x per system

\* to DIN VDE 0100 sections 410 and 430 (no permanent load) 3 phases + N+ PE (three phase current)

**Scope of delivery by WÖHR** (unless otherwise specified in the order)

Item	Description
6	Lockable main switch
7	Main switch cabinet for grid 1-5
8	Hydraulic power pack 3.0 kW with three-phase motor. Ready-wired switching cabinet with motor safety contactor
9	Branch connector
10	Operating device
11	Extra switch cabinet for grid 6-10



## Notes and directions

### Scope of application

- suitable for residential buildings, office buildings and business premises, hotels
- only for long-term users that have been instructed on how to use the system
- for frequently changing users (e.g. for office, hotel and business premises or similar):
  - performance of technical system adjustments is necessary
  - please consult with WÖHR

### Function

- one empty space per unit on entrance level
- platforms on entrance level are moved sideways
- platforms on the lower level are lifted to the empty space on the entrance level

### Numbering of the parking places

- empty space on the entrance level on the left
- numbering:

EL		2	4	6	8
LL	1	3	5	7	9

- the numbering for each unit starts with 1
- different numbering of parking places is possible at extra cost (software changes are necessary)

### Hydraulic power pack

- Arrangement of the hydraulic power pack:
  - within the unit

### Noise protection

Basis is the German DIN 4109 "Noise protection in buildings".

With the following conditions required 30 dB (A) in rooms can be provided:

- noise protection package from our accessory
- insulation figure of the construction of min.  $R'_w = 57$  dB
- walls which are bordering the parking systems must be done as single wall and deflection resistant with min.  $m' = 300$  kg/m<sup>2</sup>
- solid ceiling above the parking systems with min.  $m' = 400$  kg/m<sup>2</sup>

At differing constructional conditions additional sound absorbing measures are to be provided by the customer.

The best results are reached by separated sole plates from the construction.

#### Increased sound insulation (separate agreement):

It is based on VDI 4100 „Sound insulation in building construction“ Assessment and proposals for increased sound insulation.

Under the following conditions, 25 dB (A) can be complied with in living spaces and bedrooms:

- sound insulation package according to offer/order
- Sound insulation value of the building structure of min.  $R'_w = 62$  dB (to be performed by the customer)

Note:

User noises are not subject to the requirements (see VDI 4100, Scope - Notes). User noises are basically noises that can be individually influenced by the user of the parking systems (e.g. driving on the platform, closing of vehicle doors, engine and brake noises).

### Drainage

Water leaks into the pit:

- in the winter, up to 40 litres of snow water can possibly come with the wheel housings in just one parking process

Drainage channels:

- along the middle section of the pit
- connecting to a floor drain or drainage pit (50 x 50 x 20 cm)
- with manual emptying out of the drainage pit
- alternatively installation of a pump or drainage channel into the sewerage system, to be performed by the customer

Sideways slope drainage:

- only into a gutter
- not possible in the remaining pit section

Lengthways slope drainage:

- provided according to specified construction dimensions

Environmental safety:

- coating of the pit flooring is recommended
- installation of an oil and/or petrol separator unit between the drainage connection and the main sewerage system is recommended

### Declaration of conformity



The parking systems correspond to:

- EC Machinery Directive 2006/42/EC
- DIN EN 14010

### Switch cabinet

- Arrangement of the switch cabinet:
  - within the unit

### Temperature

- system operating range: +5° bis +40°C (with unloaded platforms lowering speed is reduced if less than +5° C)
- humidity: 50 % at +40° C
- if use in deviating temperature ranges is planned, constructive adjustments may be necessary (please consult with WÖHR)

### Lighting

- sufficient lighting of the driving aisle and of the parking places must be performed by the customer

### Fire safety

- all fire safety requirements and all mandatory equipment (fire extinguisher and fire alarm systems, etc.) must be performed by the customer
- WÖHR will provide documents on attachment points and clearances for sprinklers on request

### Railings

If walkways are arranged directly to the side or behind the systems, railings have to be provided by the customer acc. to local requirements, height min. 200 cm - this is applicable during the construction phase too.

### Maintenance

- WÖHR and all the WÖHR partners abroad provide an installation and customer service network
- regular, annual maintenance is provided subject to the stipulation of a maintenance agreement
- local requirements for electrical doors regarding the technology, maintenance and revision are not subject of our delivery. These matters have to be observed and carried out by the customer, according to the local regulations.

### Prevention of corrosion damage

- all operations listed in the WÖHR Cleaning and Maintenance Instructions are to be performed regularly (independently of maintenance operations)
- zinc-plated parts, components and platforms are to be kept clean of dirt, road-salt and any other debris (due to corrosion hazards)
- always keep the garage well ventilated and deaerated



### Surface protection

- please consider the information on surface protection!



### Tender specification

- please consider the specifications!



### Parking Place-Profile

- please consider the product information Parking Place-Profile!



### Electromobility

- please consider the product information E-charging!
- depending on the position of the charging point on the electric vehicle, collision points with protruding plugs and charging cables can occur



### Sliding doors and Operating concepts

- please consider the product information Sliding doors and Operating concepts!



### Construction formalities

- the documentation necessary for construction permit applications is provided by WÖHR on demand

### Construction alterations and/or modifications

- the right to construction or model modifications and/or variations is hereby reserved
- the right to any subsequent part modification and/or variation and amendments in procedures and standards due to technical and engineering progresses or due to environmental regulation changes is also hereby reserved